

### Description

Morini Switched LED Undershef Luminaire, complete with mains supply cable and fixing clips.

571mm Length



### General

Colour Options	White/Opal Only
Light Source	Non Replaceable LED Module
LED Expected Life	25,000 Hours
Product Warranty	2 Years from Date of Purchase
Mounting Method	Shelf/Cabinet Lighting

### Electrical Parameters

Supply Voltage	220-240V AC
Frequency	50/60Hz
Circuit Wattage	7W Including Driver
Circuit Current	0.015 Amps
Driver mA Rating	120mA
PFC	0.8PFC
In Rush Current	0.35 Amps Max

### Classifications and Approvals

Earth Class	Class ii, No Earth Required
IP Rating	IP20
Efficiency Rated (Part L)	N/A <5W
Energy Rating	A+
CE Marked	Yes
Designed In Accordance to	BSEN60598

### Installation

Mounting Bracket	Vertical or Horizontal Mounting Clips Supplied
Cable Entry	Plug & Play Mains Lead
Method of Fix	Screw Fix to Suitable Surface
Working Ambient Temp.	0°C to +30°C
Primary Connections	2 Core L&N Flex
Secondary Connections	N/A
Accessories	150mm, 300mm & 500mm Link Leads Available



### Performance

Luminous Flux	860 Lumens
Luminous Efficacy (L/pw)	122 Lp/w
CCT	3000k Warm White
CRI (Ra)	Ra75
Beam Angle	120°
Dimmable	No, Non Dimmable
Tilt/Rotate	No, Fixed Position

### Construction

Main Chassis	Polycarbonate
Trim/Bezel	N/A
Diffuser	Opal Polycarbonate
Lens	N/A
Heat Sink	Aluminium
Finish Type	White PC
Luminaire Weight	TBC

