

Description

Pasto LED Ceiling Globe Luminaire.



General

Colour Options	White Base, Opal Diffuser
Light Source	Replaceable LED Module
LED Expected Life	25,000 Hours Average Life
Product Warranty	2 Years from Date of Purchase
Mounting Method	Ceiling Mount Only
EAN	5060499510645

Electrical Parameters

Supply Voltage	220-240v AC
Frequency	50Hz
Circuit Wattage	8W (including Losses)
Circuit Current	0.04 Amps
Driver mA Rating	140mA
PFC	0.7
In Rush Current	0.45 Max Peak

Classifications and Approvals

Earth Class	Class II, No Earth Required
IP Rating	IP44
Efficiency Rated (Part L)	Yes Part L1A Compliant
Energy Rating	A+
CE Marked	Yes
Designed In Accordance to	BSEN60598

Installation

Mounting Bracket	Direct Base Mount
Cable Entry	20mm Opening On Base
Method of Fix	Screw Fix to Suitable Surface
Working Ambient Temp.	-10°C to +30°C
Primary Connections	Pre Wired with 150mm 2 Core Flex
Secondary Connections	N/A
Accessories	N/A

Performance

Luminous Flux	535 Lumens
Luminous Efficacy (L/pw)	67 L/pw
CCT	4000k Neutral White
CRI (Ra)	Ra:80
Beam Angle	360° Distribution
Dimmable	No, Non-Dimmable
Tilt/Rotate	No, Fixed Position Luminaire

Construction

Main Chassis	PMMA
Trim/Bezel	N/A
Diffuser	Opal Polycarbonate
Lens	Opal Acrylic
Heat Sink	Aluminium
Finish Type	Coloured PMMA
Luminaire Weight	0.25Kg

