

Description

Morini Switched LED Undershef Luminaire, complete with mains supply cable and fixing clips.

905mm Length



General

Colour Options	White/Opal Only
Light Source	Non Replaceable LED Module
LED Expected Life	25,000 Hours
Product Warranty	2 Years from Date of Purchase
Mounting Method	Shelf/Cabinet Lighting

Electrical Parameters

Supply Voltage	220-240V AC
Frequency	50/60Hz
Circuit Wattage	14W Including Driver
Circuit Current	0.03 Amps
Driver mA Rating	120mA
PFC	0.8PFC
In Rush Current	0.35 Amps Max

Classifications and Approvals

Earth Class	Class ii, No Earth Required
IP Rating	IP20
Efficiency Rated (Part L)	N/A <5W
Energy Rating	A+
CE Marked	Yes
Designed In Accordance to	BSEN60598

Installation

Mounting Bracket	Vertical or Horizontal Mounting Clips Supplied
Cable Entry	Plug & Play Mains Lead
Method of Fix	Screw Fix to Suitable Surface
Working Ambient Temp.	0°C to +30°C
Primary Connections	2 Core L&N Flex
Secondary Connections	N/A
Accessories	150mm, 300mm & 500mm Link Leads Available

Performance

Luminous Flux	1590 Lumens
Luminous Efficacy (L/pw)	113 Lp/w
CCT	3000k Warm White
CRI (Ra)	Ra75
Beam Angle	120°
Dimmable	No, Non Dimmable
Tilt/Rotate	No, Fixed Position

Construction

Main Chassis	Polycarbonate
Trim/Bezel	N/A
Diffuser	Opal Polycarbonate
Lens	N/A
Heat Sink	Aluminium
Finish Type	White PC
Luminaire Weight	TBC

