LED COMMERCIAL RECESSED DOWNLIGHT



PRODUCT DESCRIPTION

LED commercial fixed downlight with opal TP(a) rated diffuser. Suitable for corridors, offices, toilets and general circulation areas.

KEY FEATURES

- For recessed installation
- 2 sizes / wattages
- Back-lit design with LEDs mounted in a die-cast aluminium heat sink & body
- Driver in integral enclosure mounted on the side of the fitting
- Plug-in connector for emergency conversion pack, so any fitting can be converted to emergency later if required. Emergency conversion packs to be ordered separately, as listed below.
- Loop-in / loop-out terminals for easy installation
- Opal PC TP(a) rated diffuser in a die-cast aluminium bezel
- IP44 to front

TECHNICAL DETAILS

- Available in 2 wattages, as listed:
 - 13W (nom.), 15.7W (act.) 1,310 lumens, 83 l.lm/c.W
 - 27W (nom), 29.4W (act.) 2,500 lumens, 85 l.lm/c.W
- CRI >80
- CCT 4000K
- Non-dimmable
- Class II, but provision is made for PE to loop in/out




5 year warranty


Part number	Description
-------------	-------------

LCDL13840 180MM 1300LM 15W LED COM DOWNLIGHT 840 LCDL25840 230MM 2500LM 29W LED COM DOWNLIGHT 840


LCDLE3KIT PLUG IN EMERGENCY PACK FOR LED COM DOWNLIGHT

PHOTOMETRIC DATA






Fitting



Plug-in emergency conversion pack



Date completed by manufacturer: 14th July 2017