# Newlec\*

# Technical Data Sheet

#### LED SUSPENDED EXIT SIGN



### PRODUCT DESCRIPTION

Suspended LED exit sign with drop blade providing 3 hours of operation in the event of a mains failure.

### **KEY FEATURES**

- 3-hour maintained operation
- Supplied complete with arrow-down Euro legend

### **TECHNICAL DETAILS**

• Light source: LED

• Batteries: 4 NiCd cells. 3.6v, 600mAh

Maximum viewing distance: 30mInsulation: Class I

• Input voltage: 220-240v, 50Hz

• Approvals: CE

Newlec Helpline: 0845 123 6539



# Technical Data Sheet

### **CONSTRUCTION**

- Folded steel mounting box for fixing to ceiling with white gloss painted finish
- Extruded aluminium body, painted white
- Acrylic blade with reflective aluminium edge tape
- Supplied complete with arrow-down Euro legend on acrylic blade as shown in diagram. Alternative legends available as listed below.

### **ORDER CODES**

### **COMPLETE FITTINGS**


NLE3SES	NLE3SES NEWLEC 3W LED M WHI E3 SUS EXIT SIGN CW EURO L DOWN
ALTERNATIVE LEGENDS – EURO STYLE	
NLE3SESELU	NLE3SESELU NEWLEC EURO LEGEND ARROW UP FOR NLE3SES
NLE3SESELLR	NLE3SESELLR NEWLEC EURO LEGEND ARROW L/R FOR NLE3SES
ALTERNATIVE LEGENDS – ISO7010 STYLE	
NLE3SESILU	NLE3SESILU NEWLEC ISO 7010 LEGEND ARROW UP FOR NLE3SES
NLE3SESILLR	NLE3SESILLR NEWLEC ISO 7010 LEGEND ARROW L/R FOR NLE3SES
NLE3SESILD	NLE3SESILD NEWLEC ISO 7010 LEGEND ARROW DOWN FOR NLE3SES

Newlec Helpline: 0845 123 6539



# Technical Data Sheet

## **DIMENSIONS**



Date completed by manufacturer:

15 July 2015